

Product **Polzahl: 4, Kabellänge 2 m, Kabel: 4 x 0,34 mm², PVC, Verbindungsleitung Kabelstecker-Winkeldose**
 Area **M12-A Series 763 FOOD & BEVERAGE**
 Article number **77 3734 3729 20404-0200**

Illustration	Scale drawing	Contact Arrangement								
		<table style="margin-left: auto; margin-right: auto;"> <tr> <td>1</td> <td>braun/brown</td> </tr> <tr> <td>2</td> <td>weiß/white</td> </tr> <tr> <td>3</td> <td>blau/blue</td> </tr> <tr> <td>4</td> <td>schwarz/black</td> </tr> </table>	1	braun/brown	2	weiß/white	3	blau/blue	4	schwarz/black
1	braun/brown									
2	weiß/white									
3	blau/blue									
4	schwarz/black									

Technical data

<h3 style="color: #0070C0; margin: 0;">General features</h3> <table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">Connector Design</td> <td>Cable Connector</td> </tr> <tr> <td>Connector locking system</td> <td>bolted</td> </tr> <tr> <td>Wire gauge (mm)</td> <td>0,34 mm²</td> </tr> <tr> <td>Wire gauge (AWG)</td> <td>(22)</td> </tr> <tr> <td>Upper temperature</td> <td>105 °C</td> </tr> <tr> <td>Lower temperature</td> <td>-40 °C</td> </tr> </table>		Connector Design	Cable Connector	Connector locking system	bolted	Wire gauge (mm)	0,34 mm ²	Wire gauge (AWG)	(22)	Upper temperature	105 °C	Lower temperature	-40 °C	<h3 style="color: #0070C0; margin: 0;">Electrical parameters</h3> <table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">Rated voltage</td> <td>250 V</td> </tr> <tr> <td>Rated impulse voltage</td> <td>2500 V</td> </tr> <tr> <td>Pollution degree</td> <td>3</td> </tr> <tr> <td>Overvoltage category</td> <td>II</td> </tr> <tr> <td>Material group</td> <td>II</td> </tr> <tr> <td>Rated current (40°C)</td> <td>4 A</td> </tr> <tr> <td>Volume resistivity</td> <td>≤ 3 mΩ</td> </tr> <tr> <td>EMV compliance</td> <td>not shielded</td> </tr> <tr> <td>Degree of protection</td> <td>IP69K</td> </tr> <tr> <td>Mechanical operation</td> <td>> 100 Mating cycles</td> </tr> </table>	Rated voltage	250 V	Rated impulse voltage	2500 V	Pollution degree	3	Overvoltage category	II	Material group	II	Rated current (40°C)	4 A	Volume resistivity	≤ 3 mΩ	EMV compliance	not shielded	Degree of protection	IP69K	Mechanical operation	> 100 Mating cycles				
Connector Design	Cable Connector																																					
Connector locking system	bolted																																					
Wire gauge (mm)	0,34 mm ²																																					
Wire gauge (AWG)	(22)																																					
Upper temperature	105 °C																																					
Lower temperature	-40 °C																																					
Rated voltage	250 V																																					
Rated impulse voltage	2500 V																																					
Pollution degree	3																																					
Overvoltage category	II																																					
Material group	II																																					
Rated current (40°C)	4 A																																					
Volume resistivity	≤ 3 mΩ																																					
EMV compliance	not shielded																																					
Degree of protection	IP69K																																					
Mechanical operation	> 100 Mating cycles																																					
<h3 style="color: #0070C0; margin: 0;">Cable data</h3> <table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">material housing</td> <td>PVC</td> </tr> <tr> <td>Insulation single lead</td> <td>PVC</td> </tr> <tr> <td>Single lead structure</td> <td>42 x 0,1</td> </tr> <tr> <td>Cable sheath Ø</td> <td>4.8</td> </tr> <tr> <td>Conductor resistance</td> <td>57 Ω/Km</td> </tr> <tr> <td>Temperature range cable movable °C from</td> <td>-5</td> </tr> <tr> <td>Temperature range cable movable °C to</td> <td>105</td> </tr> <tr> <td>Temperature range cable fixed °C from</td> <td>-40</td> </tr> <tr> <td>Temperature range cable fixed °C to</td> <td>105</td> </tr> <tr> <td>Bending radius cable fixed</td> <td>min. 5 x D</td> </tr> <tr> <td>Bending radius cable movable</td> <td>min. 10 x D</td> </tr> <tr> <td>Approval 1</td> <td>UL listed</td> </tr> <tr> <td>Approval 2</td> <td>Ecolab</td> </tr> <tr> <td>Cable diameter</td> <td>4.8</td> </tr> </table>		material housing	PVC	Insulation single lead	PVC	Single lead structure	42 x 0,1	Cable sheath Ø	4.8	Conductor resistance	57 Ω/Km	Temperature range cable movable °C from	-5	Temperature range cable movable °C to	105	Temperature range cable fixed °C from	-40	Temperature range cable fixed °C to	105	Bending radius cable fixed	min. 5 x D	Bending radius cable movable	min. 10 x D	Approval 1	UL listed	Approval 2	Ecolab	Cable diameter	4.8	<h3 style="color: #0070C0; margin: 0;">Material</h3> <table border="0" style="width: 100%;"> <tr> <td style="width: 50%;">Material of contact</td> <td>CuSn (Bronze)</td> </tr> <tr> <td>Contact plating</td> <td>Au (gold)</td> </tr> <tr> <td>Material of contact body</td> <td>PP</td> </tr> <tr> <td>Material of housing</td> <td>PP</td> </tr> </table>	Material of contact	CuSn (Bronze)	Contact plating	Au (gold)	Material of contact body	PP	Material of housing	PP
material housing	PVC																																					
Insulation single lead	PVC																																					
Single lead structure	42 x 0,1																																					
Cable sheath Ø	4.8																																					
Conductor resistance	57 Ω/Km																																					
Temperature range cable movable °C from	-5																																					
Temperature range cable movable °C to	105																																					
Temperature range cable fixed °C from	-40																																					
Temperature range cable fixed °C to	105																																					
Bending radius cable fixed	min. 5 x D																																					
Bending radius cable movable	min. 10 x D																																					
Approval 1	UL listed																																					
Approval 2	Ecolab																																					
Cable diameter	4.8																																					
Material of contact	CuSn (Bronze)																																					
Contact plating	Au (gold)																																					
Material of contact body	PP																																					
Material of housing	PP																																					