



## Bulkhead Jack-Jack Adapter (Connects two plugs)



Dimensions			Max. Panel	Mounting Figure	Plating		Delta P/N
A	B	C			Body	Contact	
1.53	.86	.69	.275	59	Nickel	Silver (C)	UG-492A/U*
1.53	.86	.69	.275	59	Nickel	Silver (C)	UG-492C/U*
1.53	.86	.69	.275	59	Nickel	Silver (C)	UG-492D/U*
1.53	.86	.69	.275	59	Silver	Gold (C)	M55339/13-00492*
1.28	.80	.625	.160	59	Nickel	Silver (C)	1026-000-N591


\* Hermetically sealed, with mounting gasket.

## Panel Mounted Jack-Jack Adapter (Connects two plugs)



Dimensions		Mounting Figure	Plating		Delta P/N
A	B		Body	Contact	
1.28	.69	07	Nickel	Silver (C)	UG-414A/U

## Straight Jack-Jack Adapter (Connects two plugs)



Dimensions		Plating		Delta P/N
A	B	Body	Contact	
1.28	.44	Nickel	Silver (C)	UG-914/U
1.28	.44	Silver	Gold (C)	M55339/16-00914
1.28	.44	Nickel	Gold (C)	1028-000-N001-3

(C) in contact plating column indicates captive contact. • See page 6 for alternate body plating information.  
See page 203 for mounting dimensions.